



Model HHS Specifications

SPECIFICATIONS

Bottom Thread	4-1/2", 5-1/2" & 7" O.D. 8rd	8-5/8" O.D. 8rd	9-5/8" O.D. 8rd	10-3/4" O.D. 8rd
Bottom Connection	Female	Female	Female	Female
Working Pressure	1500 PSI	1500 PSI	1500 PSI	1500 PSI
Test Pressure	3000 PSI	3000 PSI	3000 PSI	3000 PSI
Max. Slip Load	85,000 lbs.	100,000 lbs.	100,000 lbs.	100,000 lbs.
Cap Flange	Modified Flange	Modified Flange	Modified Flange	Modified Flange
Gland Ring Material	Ductile Iron	Ductile Iron	Ductile Iron	Ductile Iron
Inner String	2-3/8", 2-7/8" & 3-1/2" (3-1/2" available in 7" ONLY)	2-3/8", 2-7/8", 3-1/2" 4-1/2" & 5-1/2"	2-3/8", 2-7/8", 3-1/2" 4-1/2", 5-1/2" & 7"	2-3/8", 2-7/8", 3-1/2" 4-1/2", 5-1/2" & 7"
Suspension	Slip	Slip	Slip	Slip
Side Outlet	2" LP	2" LP	2" LP	2" LP
Minimum Bore	4.090/5.012/6.551"	8.000"	8.875"	9.938"
Body Material	Ductile Iron	Carbon Steel	Carbon Steel	Carbon Steel
Height	14-1/2"	13-1/2"	16"	16"
Weight	145 lbs.	195 lbs.	265 lbs.	265 lbs.

CABLE SPECIFICATIONS

Cable Size	Flat Cable	Round Cable
1	0.289	1.28
2	0.655	1.21
4	0.562	1.01
6	0.050	0.862