



“NEW” 6033 RotaTorq™

The 6033 RotaTorq™ provides customers with a next generation rod rotator designed for today's challenging horizontal well profiles. The “NEW” rod rotator is manufactured with premium bearings and heavy-duty components to deliver more torque. The 6033 RotaTorq offer operators increased runtimes to reduce downtime and maintenance costs.

Specifications & Features:

- ✓ 60,000 lbs. Max. recommended load
- ✓ 400 ft./lbs. Max. output torque
- ✓ 120 lever pulls to 90° for complete revolution
- ✓ 8.5” Required opening between bridle lines
- ✓ Longer handle with clevis to reduce cable failure
- ✓ Robust one-way bearing
- ✓ **PATENT PENDING TECHNOLOGY**

Maintenance:

- ✓ Internally sealed working components
- ✓ Greasing intervals twice a year max.
- ✓ Only replacement item is handle assembly

6033 RotaTorq™



→ Side-by-Side ←
**4033 Pro-Torque &
6033 RotaTorq**



“Customer Corner”

- The 6033 RotaTorq has been extensively field tested over several years.
- Extends tubing and rod string life to protect your investment in the rod string.
- Effectively reduces paraffin buildup, decreasing chemical program costs.
- Maximize rod guide spend due to rotating and wearing 100% of guide fins versus 25%.
- 2-year warranty on all 6033 RotaTorq. Longest rod rotator warranty in the industry.

Wellhead Systems Inc.
PO Box 129
Hill City, KS. 67642

Phone: 866-478-2537
Fax: 785-421-2256
www.wellheadsystems.com

“Make Your Connection with WSI”